

# Nanodrop II and Nanodrop Express

## LOW VOLUME AUTOMATED PIPETTOR


**BioNex**  
Solutions Inc.

- *Low volume (100 nL and above), high-precision dispensing*
- *Aspirate and dispense with individual channel volume control*
- *Capable of dispensing a different volume into every well*
- *Pipette up to 8 or 16 reagents simultaneously*
- *Valve-free flow path*



For a complete high-throughput solution for low-volume, high-precision pipetting, try the 8-channel Nanodrop II or the 16-channel Nanodrop Express Auto Pipettors. Each system has interchangeable, fixed-tip heads (1x8 or 2x4 configurations for the Nanodrop II and 1x16 or 2x8 configurations for the Nanodrop Express) and comes with two plate positions that enable applications such as assay miniaturization, DNA normalization, method development, PCR and NGS reaction setup, or protein crystallography.

The Nanodrop pipetting technology aspirates and dispenses a broad range of liquids, including DMSO, and features the Nanobuilder software system that enables a wide range of applications and data manipulation. This patented technology isolates the solenoid dispense actuators from the sample path to assure long life and easy, low-cost maintenance — even with regular use



## Key Features and Benefits

- Sample transfer and bulk reagent addition on the same platform
- Aspirate and dispense with individual channel volume control
- Interchangeable 1x8 to 2x4 head; or, 1x16 to 2x8 heads
- Micro solenoid valves for fast, precise low-volume applications and mixing
- Exceptional dynamic range (nanoliter to milliliter)
- Valve-free fluid path for outstanding reliability
- FEP, SS, sapphire wetted parts compatible with commonly used solvents
- 96-, 384- and 1536-well plate formats, irregular and flat plate formats supported
- Deep well and crystallography plates supported
- Easy to program, easy to automate
- Simple cleaning and maintenance

## Applications

- PCR template and cocktail additions
- DNA normalization
- Assay miniaturization
- Serial dilution
- Cell plating
- Sample transfer
- Bulk reagent addition
- Protein crystallography screens
- MALDI plate spotting

## Performance Specifications

|                            |  |
|----------------------------|--|
| <b>Dispense Range:</b>     | Microsolenoids: 0.1–80 $\mu$ L<br>Syringe: 5–500 $\mu$ L                   |
| <b>Aspirate Range:</b>     | 500 $\mu$ L Syringe: 5–500 $\mu$ L<br>1000 $\mu$ L Syringe: 5–1000 $\mu$ L |
| <b>Dispense Precision:</b> | $\leq$ 10% at 100 nL<br>$\leq$ 7% at 200 nL<br>$\leq$ 5% at 1 $\mu$ L      |
| <b>Residual Volume:</b>    | < 3 $\mu$ L /channel   |

## General Specifications

| Nanodrop II Automated Pipettor |  |
|--------------------------------|--|
| <b>Number of Channels</b>      | 8  |
| <b>Height</b>                  | 330.2 mm [13 in]                             |
| <b>Width</b>                   | 279.4 mm [11 in]                             |
| <b>Depth</b>                   | 457.2 mm [18 in]                             |
| <b>Weight</b>                  | 11.3 kg [25 lbs]                             |
| <b>Automation Control</b>      | .NET DLL components                          |
| <b>Interface</b>               | RS-232 connectivity,<br>Nanobuilder software |

| Nanodrop Express Automated Pipettor |  |
|-------------------------------------|--|
| <b>Number of Channels</b>           | 16   |
| <b>Height</b>                       | 330.2 mm [13 in]                             |
| <b>Width</b>                        | 558.8 mm [22 in]                             |
| <b>Depth</b>                        | 457.2 mm [18 in]                             |
| <b>Weight</b>                       | 22.7 kg [50 lbs]                             |
| <b>Automation Control</b>           | .NET DLL components                          |
| <b>Interface</b>                    | RS-232 connectivity,<br>Nanobuilder software |

For Research Use Only. Not for use in diagnostic or therapeutic procedures.

LIT-50004 Rev. E Effective 2018-10